



P1.25

INDOOR LED DISPLAY



- Ultra-Fine Pixel Pitch – 1.25 mm spacing for sharp, detailed indoor visuals.
- Wide Viewing Angle – Clear and consistent colors from all directions.
- Superior Color Performance – 3-in-1 SMD LEDs for vibrant, realistic images.
- Compact & Lightweight – Easy to install in tight spaces.





LED Display Parameters

P1.25 Indoor Full Color Display SMD1010(1R1G1B)

Item	Parameter
Model Number	P1.25
Module Size	320 × 160 mm
Pixel Pitch	1.25 mm
Pixel Density	640,000 pixels/m ²
Color Temperature	3500 K – 9300 K
LED Package	SMD1010
Module Resolution	256 (W) × 128 (H) dots
Optimal Viewing Distance	1.5 m – 3 m
Aspect ratio	16:9
Module Thickness	15 mm
Module Weight	0.4 kg
Pixel Configuration	3-in-1 SMD
Viewing Angle	160°(H)/ 140°(V)
Brightness Uniformity	97%
Brightness (White Balance)	≥ 600-1200 cd/m ²
Contrast Ratio	5000:1
Refresh Frequency	≥ 3840 Hz
Ingress Protection (Front/Rear)	IP50
Maintenance Type	Front Service
Life Span	≥ 100,000 hours



Contact Us

KAN Universal Pvt. Ltd.
367, First Floor, Kothi Wala Bagh,
Ashok Vihar Phase 4, Delhi-110052
www.kanuniversal.com
info@kanuniversal.com | +91-88788 72022

